Hybrid Design Electrothermal Polymeric Microgripper with Integrated Force Sensor

V. Vidyaa¹

¹Jawahar Engineering College, Affliated to Anna University, Chennai, Tamil Nadu, India

Abstract

Microgrippers are typical MEMS devices used to pick, hold and transport micro-objects. Microgrippers are widely used in the field of micro-assembly, micro-surgery and manipulation of micro-particles. Thermal microgrippers are widely used for large displacement, high accuracy and repeatability. In this paper, a hybrid design electrothermal microgripper (Figure 1), based on Poly Methyl Methacrylate (PMMA) with integrated force sensor is designed and analysed using COMSOL Multiphysics software. The new design is designed by combining asymmetric arm structure and bi-layer structure to minimize the undesired out of plane displacement of the microgripper. The in-plane, out of plane and curl displacements, stress, strain and temperature has been analysed and the results are discussed (Figure 2). A piezoelectric force sensor (Figure 3), based on Poly Vinylidene Fluride (PVDF), which is to be integrated with microgripper to resolve the gripping force exerted by the microgripper on the micro-objects, is also designed and analysed. The force sensor is analysed for charge density for various gripping forces, stress, strain and displacements along X,Y, and Z axis (Figure 4). The hybrid design gives 1.6 µm in-plane displacement and 0.3 µm out of plane displacement at 0.1 V applied voltage. The maximum temperature of the microgripper is 323 K. The fabrication method for the hybrid design electrothermal polymeric microgripper is discussed.

Reference

[1] A. F. Marques et al, Modelling the electrostatic actuation of MEMS: State of the Art (2005), IOC-DT-P-2005-18, pp 1-33

[2] S.K. Nah, Z.W. Zhong, A Microgripper using Piezoelectric Actuation for Microobject Manipulation, Sensors and Actuators A133 (2007) pp 218-224.

[3] C.S Jeon et al, Fabrication and Characteristics of out of plane piezoelectric microgripper using MEMS processes, Thin Solid Films 515 (2007) pp 4901-4904.

[4] M.N.M. Zubir et al, A New Design of piezo electric driven compliant based micro gripper for micro manipulation, Mechanism and Machine Theory 44 (2009) pp 2248-2264.

[5] M.N.M. Zubir et al, Development of a Novel Flexure based micro gripper for high precision micro object manipulation, Sensors and Actuators A150 (2009) pp 257-266.

[6] O. Millet et al, Sensors and Actuators (2004) pp 1-8

[7] S.A. Bazaz et al, Design simulation and testing of electrostatic SOI MUMPs based microgripper integrated with capacitive contact sensor, Sensors and Actuators, Accepted Manuscript, (2010) pp 1-31.

[8] N. Chronis, L.P. Lee, Electrothermally Activated SU-8 Microgripper for Single Cell Manipulation in Solution, Journal of Micro-ElectroMechanical Systems, Vol 14, pp 857 -863 (2004).

[9] M.A. Greminger et al, A Four Degree of Freedom MEMS microgripper with Novel Bidirectional thermal actuators, 2005 IEEE International Conference on Intelligent Robots and Systems.

[10] B.E. Volland et al, Duo-action electro-thermal microgripper, Microelectronic engineering 84 (2007) pp 1329 – 1332.

[11] C. Elbuken et al, Design and analysis of a polymeric photo-thermal microactuators, Sensors and Actuators, A147 (2008) pp 292 – 299.

[12] J. Hosek, M. Danek, Full metal microgripper made by Electro discharge technique,

MECAHITECH'10 international conference (2010) pp 155-162.

[13] D.S.W. Park et al, A Sub-micro metallic electro thermal gripper, Microsys Technol (2010) 16, pp 367-373.

[26] D.H. Kim et al, A super elastic alloy microgripper with embedded electromagnetic actuators and piezoelectric force sensors: a numerical and experimental study, Smart materials and structures, 14 (2005), pp 1265 – 1272.

[14] M.M. Bilderen et al, A mechanically actuated silicon micro- gripper, for handling micro and nano-particles Microelectronic Engineering 83 (2006) pp 1382-1385 .

[15]Y Choi et al, Mechanically driven microtweezers with integrated microelectrodes, Journal of Micromechanics and Micro engineering, 18 (2008) pp 1-9.

[16] J.A. Martinez, R.R. Pannepucci, Design Fabricaton and Characteristics Florida Conference on Recent Advances in Robotics (2007) pp 1-6.

Figures used in the abstract




Figure 1: Hybrid design electrothermal polymeric microgripper




Figure 2: Results of microgripper



Figure 3: Piezoelectric force sensor




Figure 4: Results of force sensor